

IPC 7



15" Industrial PC with MS® Windows® XP Pro/Emb, WES7

Features

- 15" TFT-Display, 450 cd/m²
- Resistive touch screen with high breakage resistance
- Fully rugged, IP 67 for the complete system
- WLAN with optimum transmission characteristics
- More than 70 mounting variations (stationary + mobile use)
- Extreme temperature cycles, freezer capable
- Extreme shock & vibration

Introduction

DLoG IPC 7/215 is an industrial PC for use in production and logistics, combining industrial capability, simple operation and excellent visualization within one unit. With its rugged construction it can easily withstand extreme mechanical, electrical, chemical and thermal environmental conditions.

Specification

System	CPU	Intel® Celeron® M 800 MHz Low Voltage, 1 GHz Ultra Low Voltage or Intel® Core™ Duo L2400 Low Voltage 1.66 GHz
	Memory	512 MB up to 1 GB DDR2
	Hard disc drive	40/60 GByte (Shock/Vibration up to class 5M2)
	CompactFlash	Type I/II up to 16 GByte
Housing		coated aluminium, fanless design
Dimensions/Weight		326 x 395 x 121 mm / 12.8 x 15.6 x 4.8 in
		8.3 kg / 18.3 lbs
Display		15" Color-TFT, XGA 1024 x 768, 450 cd/m² (brighter displays on request)
Touch Screen		DLoG-specific resistive Touch Screen
Software	Operating System	MS® Windows® XP Professional, XP Embedded, WES 7 Linux upon request
	Emulations	VT100, VT220, IBM 5250, TN 3270, Freefloat Access One, Citrix Client®
Interfaces	Serial	2 x RS-232, alternatively 1 x RS-232 or 1 x RS-422/485 COM 1 optionally 5 V or 12 V
	USB	2 x USB 2.0 (HI-SPEED™)
	PS/2	keyboard/mouse, standard 6 pol. Mini-DIN connector
	LAN	Ethernet 10/100 MBit/s
Network	WLAN	IEEE 802.11 a/b/g/n
Ports	PCI	2 x PCI Slot 32 Bit, Rev. 2.2 compatible for short card (max. length 5.55 in)
	Internal Cardbus*	1 Cardbus for type I/II (16/32 Bit) or
	PCIe MiniCard*	1 x PCIe MiniCard (* both features upon request)
Power supply (internal)	AC	110/230 VAC, 100 W, 50 to 60 Hz
	DC	24/48 VDC, 60/100 W, galvanic. isolated; handles voltage sags to 10 VDC for up to 20 sec 12 VDC, 100 W, galvanic. isolated; handles voltage sags to 5 VDC for up to 20 sec
Environmental	IP protection class	IP 67 and IP 66 (contains IP 65 and IP 54)
	Certifications	CE/FCC Class A
	Operating temperature	0 to +50 °C / 32 to 122 °F; with optional temp. extension: -10 to +50 °C / 14 to 122 °F
	Relative humidity	10 to 90% @ 40 °C, non condensing
	Shock/Vibration	Class 5M3 according DIN EN 60721-3-5 and MIL-STD 810F (US Highway Truck)

Information in this document is subject to change without prior notice. The software and hardware designations used in this text are in most cases also registered trademarks and are thus subject to law.