

FT-150

Fanless



- Compact All-in-One M/B Design with rich I/O
- Fanless design for silent operation
- Extremely solid and reliable structure suitable for heavy duty environment
- Flexibility design suitable for various applications
- 15" TFT LCD available with 5-wired resistive touch panel technology
- IP65 water-proof sealing enclosure around the bezel
- Power switch and LCD brightness control panel
- Hidden connector and power cable design
- Optional CF socket functionality for thin client Application
- Removable HDD for easy maintenance

15" High Performance
All-in-One Touch Terminal

LONGSHINE POS

RoHS CE FC

FT-150 Fanless



Removable base and wall mounting capability with 75mm VESA holes

IP65 Water-Proof sealing enclosure around the bezel



Modularized 2 x 20 VFD customer display



Tilt angle 0° ~ 75°
Adapt to operation in any environment



Removable HDD design for easy maintenance



3-Track magnetic stripe reader for membership management or operator identification

Specifications

Model Name	FT-150	
Motherboard	PS960GLE	PS965GME
CPU	Intel Celeron Mobile 2.0GHz	Intel Core 2 Duo Mobile
Memory	DDR2 533/677 MHz x 2 (Max. 4GB)	
Vedio	960GLE Integrated Graphic Engine	965GME Integrated Graphic Engine
Ethernet	10/100/1000 Mbps Ethernet	
Display	15" XGA TFT	
LCD Size	250-350 cd / m	
Brightness	1024 x 768	
Resolution	Taiwan made 5-wired or ELO Resistive Touch (RS-232 or USB Interface)	
Touch Screen Type	0-75 degree	
Tilt Angle	1 x 2.5" SATA HDD	
Storage Device	1 x Compact Flash II Socket	
HDD	Total 6 Serial ports, each port supply +5V / +12V Power	
Flash Memory	2 x Internal, 4 x External	
I/O ports	1 x, support SPP/EPP/ECP	
Serial Port	Total 6 USB ports (USB 2.0)	
Parallel port	4 x External, 2 x Internal	
USB Port	1 x mini-Din Keyboard port	
PS/2 Port	1 x Mouse port	
VGA Port	1 x VGA port (for second screen)	
Ethernet Port	1x, 10/100/1000 Base T Ethernet, supports Wake-From-LAN	
Cash Drawer Port	2 x RJ-12	
Audio Port	1 x Audio Line-out port	
Expansion Slot	1 x Mic-in port	
Physical Dimension	1 x Mini PCI Slot	
Dimension (mm)	351(W) x 288(D) x 329(H)	
Others	Second LCD screen without Touch	
Optional Integrated Device	VFD Customer Display	
	MSR and/or Fingerprint sensor	
	3-in-1 MSR/ ICC/ IBT Multi-tag Reader	

LONGSHINE Technologie (Europe) GmbH
No. 945 Boai Street, Jubei City, Hsinchu, Taiwan 302
Germany Division:
An der Strusbek 9, D-22926 Ahrensburg, Germany
Tel: +49 (0) 4102 - 49220 Fax: +49 (0) 4102 - 40109
Email: info@longshine-pos.com www.longshine-pos.com

POS
RoHS CE FC