

POS 325



POS 325 Series

The POS 325 series is a slim, small footprint design for the hospitality and retail industries. Its glossy back cover with a polished decoration ring gives it an elegant look. A variety slim type peripherals perfectly fit in the ID design. POS325 supports multiple platforms from Cedar View to Ivy Bridge Mobile processors which can meet different performance requirements. A true flat touch panel prevents water and dust incursion and provides the customer with the best touch experience.

- 15" display with True Flat touch technology
- A fanless design to reduce noise and prevent dust inside the unit
- Intel CedarView D2550 or Ivy Bridge Mobile Processors supported
- HDD easy to swap
- Slim type peripherals design



Features



15" LED LCD display with or normal resistive technology



A fan-less design to reduce noise and prevent dust inside the unit



15" 2nd display supported





HDD easy to swap



Main board removable for easy service



Slim type peripherals, MSR, VFD, iButton



Specification

Model Name	POS325	
Motherboard	C56	C76
Processor	Intel CedarView D2550 processor 1M Cache, 1.86 GHz, 10W	Intel Ivy Bridge Celeron 1007U Dual Core 1.5 G, LLC 2M, 22nm, 17W
Chipset	CPU integrated graphic + NM10, 2W	CPU integrated graphic + HM76, 4.1W
System Memory	1 x DDR3 SO-DIMM up to 4GB, 1066MHz	1 x DDR3 SO-DIMM up to 8GB, 1600MHz
Graphic Memory	DX9, Graphic core speed at 640MHz	Intel HD graphic DX 11 and OCL1.1
LCD Touch Panel		
LCD Size	15" TFT LCD	
Brightness	250~300 cd/m ²	
Resolution	1024x768	
Touch Screen	Resistive touch / True flat resistive touch	
Tilt Adjustment	0° ~ 90°	
Storage Device		
Hard Drive	One 2.5" slim SATA HDD bay	
Flash Memory	SATA SSD flash card (same location as HDD, Option)	
Expansion		
miniPCI-E Socket	1	
External I/O Ports		
USB	4 x USB Type A (USB 2.0)	6 x USB Type A (USB 3.0 / 2.0 x 2, USB 2.0 x 4)
	4 x RJ45 COM ports	3 x RJ45 COM ports
Serial Port	(COM1 standard RS232; COM2/3/4 powered RS232; COM2 default 0V; COM3 default 5V; COM4 default 12V by BIOS setting)	(COM1/2/3 powered RS232; COM1 default 5V; COM2 default 5V; COM3 default 12V by BIOS setting)
GigaLAN (10/100/1000)	1 (RJ45)	
Parallel	1	
Cash Drawer	1 (RJ11)	
2 nd VGA	1 (DB15 Female)	
DC Jack	1	
Power Switch	1	
Audio		
Built in Speaker	2W x1 (Option)	
Control / Indicator		
Power Button	1	
Power		
Power Supply	65W/19V-4 pin Lock	90W/19V-4 pin Lock
Peripheral (option)		
MSR	3 Tracks (USB)	
iButton	iButton (USB)	
Finger Print Reader	Finger Print Reader (USB)	
Second Display	Option 15" 2 nd display without touch	
Customer Display	LCM display 2 x 20 characters (USB) / Tilt angle: 10° (Up), 24° (Down), 25° (Right), 25° (Left)	
Certificate		
EMC & Safety	FCC Class A / CE Mark / LVD	
Environment		
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	
Humidity	20% ~ 85% RH non-condensing	
Dimension (WxDxH)	360 x 210 X 360 mm (14.2" x 8.3" x 14.2")	
Weight	4.8kg (10.6lbs)	
OS Supported	Windows Embedded POSReady 2009, Windows XP Professional for Embedded, Windows 7	

Product specifications subject to change without prior notice.

©2013 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.

1307 - P325a



FLYTECH TECHNOLOGY CO., LTD.

No. 168, Sing-ai Rd., Neihu District,
Taipei City 11494, Taiwan, R.O.C.
Tel: 886-2-8791-4988
Fax: 886-2-8791-4966
E-mail: sales@flytech.com.tw
www.flytech.com

U.S.A. - California

728 Charcot Ave, San Jose, CA 95131, U.S.A Tel: 1-510-257-5180 Fax: 1-510-257-5181 E-mail: sales@flytech.com
China - Shanghai
 3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China
 Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 http://www.flytech.com.cn E-mail: sales@flytech.com.cn
China - Hong Kong
 Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Road, Kowloon Bay, Kowloon, Hong Kong.
 Tel: 852-3525-5800 Fax: 852-2751-7447 E-mail: sales@flytech.com.hk