



ProLite T1732MSC-B1

The ProLite T1732MSC 17" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours. Analogue and DVI inputs are available for flexible connectivity along with USB for the Touch Interface. The multi-touch function is supported only under Windows® 7 and 8.

DISPLAY CHARACTERISTICS

Diagonal	17"
Touchtechnology	projective capacitive, multitouch (2 compatible touch points - supported only under Windows® 7/8), activated by finger
Panel	TN
Glass hardness	7H minimum
Display area h x w	270.5 x 338 mm; 10.6" x 13.3"
Response time	5 ms
Static contrast	1 000 : 1 with touch panel
Brightness	225 cd/m² with touch panel
Viewing zone	horizontal/vertical: 160° / 160°; right/left: 80° / 80°; up/down: 80° / 80°
Display colour	16.7 million
Pixel pitch h x v	0.264 x 0.264 mm
Native resolution	1280 x 1024 (1.3 megapixel)
Horizontal sync	31,4 - 80 KHz
Vertical sync	56 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	5 : 4
Light transmittance	90%

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	25 W typical; max. 2 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	387 x 342 x 202 mm
Weight	5.6 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA
Digital input connector	DVI-D
Inputs	USB (for touch connectivity)

SPECIAL FEATURES

Controls	On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power)
User controls	contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Speakers	2 x 1 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Safety	CE, CB, TÜV-Bauart, VCCI, GOST-R, IP54
Tilt angle	90° up; 5° down
VESA mounting	100 x 100 mm
Colour	Black, White

ACCESSORIES

Driver	multi-touch: Windows7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX)
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), screw, quick start guide, safety guide