

Data Sheet

LCS-10N-B

10" Digital Signage with barcode scanner

Performance . Quality . Compact

LONGSHINE's LCS-10N-B was designed for digital signage application which requires performance and installation feasibilities. LCS-10N-B can be flexibly vesa wall / rack mounted in various environments.

Your total cost of ownership will also be significantly reduced through competitive hardware costs, improved efficiencies and minimal administration efforts. Finally, high product quality ensures a long lifecycle.



Hardware

CPU: Cortex-A9, Dual Core, up to 1.2GHz

System Memory: 1GB DDR3 SDRAM

Internal Storage Memory: 4GB NAND Flash

External Storage Memory: SD Card (SDHC Class10 compatible)

LCD: 10.1" 1024X600 digital TFT LCD

Touch Panel Type: 5 point capacitive multi-touch type

Amplifier, Speaker:

- Speaker unit: 3W+3W
- Amplifier 3W+3W
- Save the set-up volume and keep the value at the time of power off and on.

Clock Battery (for RTC): Lithium-ion non-rechargeable coin battery

LED:

- [power supply ON] , [timer standby], and [power supply OFF] modes are supported.
- Power supply ON: Green
- Timer standby: Orange
- Power supply OFF: LED light off

Wireless Communication Specification

- Wi-Fi: IEEE 802.11b/g/n (optional)

Ethernet Communication Specification

- 10/100Mbps LAN RJ45 built-in

Dimensions without barcode scanner:

Width: 274.5mm

Height: 160.5mm

Depth: 23.5mm

Technical Specifications

| | | |
|------------------------|----------------------|---|
| Display | TFT LCD | 10.1" (16:9 diagonal) inch configuration |
| | Number of Pixel | 1024 RGB (H) x 600(V) |
| | Back-light | LED Side-light type |
| Media format | Video | MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV |
| | Audio | MP2, WMA, WAV, AAC, OGG, ASF |
| | Picture | JPG, BMP, GIF |
| I/O | SD card slot | SD card (SDHC Class10 compatible) |
| | USB | USB 2.0 host type A×1 |
| | Micro USB | Micro USB 2.0 × 1 |
| | Mini HDMI | Mini HDMI out, Type C ×1 |
| | Module slot | USB 2.0 x 1 |
| Speaker | High quality speaker | 3W×2 |
| Power | AC/DC adapter | 12V/2A AC/DC adapter |
| Wireless Communication | Wi-Fi | 802.11 b/g/n (optional) |
| Ethernet | RJ45 | 10/100Mbps LAN |
| Camera | Front | Front: 2M pixels (optional) |
| Function keys | Key button | +, -, Up, Down, Menu/Enter |
| Barcode scanner | Barcode scanner | 2D Barcode scanner |

Features and specifications are subject to change without prior notice.

Barcode Scan Specifications

| | | |
|-----------------|---------------------------|---|
| Symbols | 2D | PDF417, QR Code(Model 1/2), DataMatrix(ECC200, ECC000, 050, 080,100,140) |
| | 1D | Code128, EAN-13, EAN-8, Code39, UPC-A,UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code93, UCC/EAN-128, GS1 Databar, etc. |
| Precision | ≥ 4mil | |
| Symbol Contrast | ≥ 30% | |
| Scan Angle | 37.5°H, 24.5°V | |
| Roll | 360°@ 0°Pitch and 0° Skew | |
| Skew | ±50°@ 0°Roll and 0° Pitch | |
| Pitch | ±50°@ 0°Roll and 0° Skew | |

Image Capture Specifications

| | |
|--------------|---------|
| Image Sensor | CMOS |
| Resolution | 752*480 |
| Interface | USB |

Illumination Specifications

| | |
|--------------|-----------------------|
| Light Source | LED (620 nm - 630 nm) |
|--------------|-----------------------|

Electrical and Mechanical Specifications at 23 degree

| | |
|-------------------------|------------------|
| Power Consumption(Max) | 1.485 W(@3.3VDC) |
| Voltage | DC3.2V-DC5.5V |
| Max Working Current | 450 mA(@3.3VDC) |
| Average Working Current | 330 mA(@3.3VDC) |
| Idle Current | 75 mA(@3.3VDC) |
| Deep Sleep Current | 900 uA(@3.3VDC) |
| Dimensions (L*W*H) | 69 *30*46 mm |
| Weight | 36.5g |

Environment Specifications

| | |
|-----------------------|---------------------------|
| Operating Temperature | -15°C - +55°C |
| Storage Temperature | -40°C - +80°C |
| Humidity | 5% - 95% (Non-condensing) |
| Ambient Illumination | 0 ~ 100,000 LUX |

External Interface

- SD card slot
- Key button (+, -, Up, Down, Menu/Enter)
- USB interface:
 - USB host type A port (USB 2.0 high speed 480Mbps) x 1
 - Micro USB port (USB 2.0 high speed 480Mbps) x 1
 - Module slot (USB 2.0 interface high speed 480Mbps) x 1
- Mini HDMI interface: Mini HDMI out, Type C x 1
- Ethernet RJ45 10/100Mbps connector
- Power switch
- AC adapter port
- Metal-fittings mounting screw holes: four places

Product Outlook

Front:



1. Camera (optional)

Top:



- 2. LED
- 3. SD card slot + cover
- 4. Menu / Enter button
- 5. Function keys (up / down)
- 6. Function keys (vol+ / Vol-)

Back:



- 7. Speakers
- 8. Vesa mounting holes
- 9. DC In
- 15. Add-on Module Slot

Bottom



- 9. DC In
- 10. Ethernet RJ45 port
- 11. USB type A
- 12. Micro USB
- 13. Mini HDMI out
- 14. Power switch
- 15. Add-on Module Slot



16. 2D barcode scanner

Software

OS: Android 4.1.x, Jelly Bean

Flash Support : Adobe Flash 10.2 supported

Pre-installed Applications

| LCS-10N-B Current Pre-install App List (App with Red * can't be deleted.) | |
|--|---|
| App name | Description |
| *AppInstaller.apk | Applications install tool |
| *ApplicationProvider.apk | Applications to support services |
| *BackupRestoreConfirmation.apk | Backup and Restore confirmation |
| Browser.apk | Android default Browser |
| Calculator.apk | Calculator |
| Calendar.apk | Calendar |
| CalendarProvider.apk | Calendar program support service |
| Camera.apk | Android Camera |
| *CertInstaller.apk | Certificate Services |
| Contacts.apk | Contacts |
| *ContactsProvider.apk | Contacts data Storage Service |
| *DefaultContainerService.apk | The default directory services |
| DeskClock.apk | Take alarm clock |
| *DownloadProvider.apk | download management |
| *DownloadProviderUi.apk | download management UI |
| *DrmProvider.apk | The protected of Drm data storage service |
| Email.apk | Android default E-mail |
| Exchange.apk | E-mail service |
| FileBrowser.apk | File Browser |
| Gallery2.apk | View Pictures |
| *HoloSpiralWallpaper.apk | Live Wallpaper |
| HTMLViewer.apk | HTML explorer |
| *KeyChain.apk | Key authentication |
| *LatinIME.apk | Latin IME |
| *Launcher2.apk | Native desktop |
| LiveWallpapers.apk | Live Wallpapers |
| *LiveWallpapersPicker.apk | Live Wallpaper |

| | |
|-----------------------------|----------------------------------|
| MagicSmokeWallpapers.apk | The application of the wallpaper |
| *MediaProvider.apk | Media data storage service |
| *Music.apk | Music |
| *MusicFX.apk | Music & Audio app |
| NoiseField.apk | Live Wallpapers of Bubbles |
| *PackageInstaller.apk | Program Installation |
| PhaseBeam.apk | Live Wallpaper app |
| *Phone.apk | Phone |
| PicoTts.apk | Text speech convert engine |
| *Protips.apk | Desktop plugin little green men |
| *Provision.apk | Boot loader program |
| QuickSearchBox.apk | Quick Search Box |
| *Settings.apk | Settings |
| *SettingsProvider.apk | Set service program |
| *SharedStorageBackup.apk | Share data backup service |
| SoundRecorder.apk | sound recorder |
| Superuser.apk | Authorized Program |
| *SystemUI.apk | Android Status bar |
| *TelephonyProvider.apk | Dial-up records storage service |
| *UserDictionaryProvider.apk | The user data dictionary service |
| *VideoPlayer.apk | Amlogic Video Player |
| VisualizationWallpapers.apk | Visualization Wall papers |
| VpnDialogs.apk | VPN LAN service |

Playback Format Support

| | | |
|-------|-------|---|
| Media | Video | MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV |
| | Audio | MP2, WMA, WAV, AAC, OGG, ASF |
| Image | | JPG, BMP, GIF |

More information

Longshine Services

In addition to model from Longshine LCS-10N-B, Longshine provides a wide range of platform solutions. Combine reliable Longshine products with the best services, know-how and worldwide partnerships.

Longshine Hardware Portfolio

Longshine offers a full portfolio of IT hardware ranging from networking, POS, digital signage and e-books. This allows customers to single source from one vendor to ensure installation compatibility and reduce response times for technical enquiries, and changing business requirements.

POS Products

<http://pos.longshine.de>

Networking Products

<http://network.longshine.de>

E-Book

tolino@longshine.de

Digital Signage Products

info@longshine.de

More information

To learn more about Longshine LCS-10N-B and other digital signage products, please contact your Longshine sales representative or Longshine Business partners, or visit our website. www.longshine.de

LONGSHINE VISION

It's our policy to be open minded and mechanical flexible to support our Business partners, and to also secure projects from different technical enquiries/opportunities. By listening and understanding to market needs, we also aim to contribute technical knowledge to continuously improve and create standard models with high CP values. To become a Longshine Business partner, please contact via info@longshine.de



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2014 LONGSHINE Technologie GmbH.

Disclaimer

Part number LCS-10N-B the Stylized Longshine Logo are trademarks or registered trademarks of LONGSHINE Technologie GmbH. Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. All other trademarks are property of their respective owners.

Contact

LONGSHINE Technologie GmbH
Corporate Headquarters
An der Strusbek 9, 22926 Ahrensburg, Germany
TEL: +49 4102 49220 FAX: +49 4102 40109
www.longshine.de
info@longshine.de

Part number LCS-10N-B and the Stylized Longshine Logo are trademarks or registered trademarks of LONGSHINE Technologie GmbH. All other trademarks are the property of their respective owners. All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2014 LONGSHINE Technologie GmbH.