

10.1" ALL-IN-ONE MINI POS

With printer integrated

Features:

Maximise the usage, minimize the cost

Platforms Braswell covers all needs

■ Flexibility of power

Touch type

■ 10.1" Projected Capacitive Touch

Zero bezel design

water and dust proof sealing for business usage

Space saving and with printer integrated design

■ Easily configured on the counter to suit maximal needs and demands of the user

Fanfree design

Contributes to a pleasant quiet working environment

Performance

Fits into any POS software environment with relative ease

■ 10F-BWA1 provides a wide range of platforms to cover all software needs















System Specifications	
CPU	Intel® Pentium® Celeron N3160 or Pentium N3710 SoC
System Memory	DDR3L 1600 4GB Standard
Graphics	Intel® HD Graphics Gen8
Audio/Visual	Realtek ALC282
Display	10.1 " TFT-LCD /1024x600 (LED backlight)
	Touch Screen: 10.1" Projected Capacitive touch
Storage	64GB M.2 2242 SSD MLC
Color	Black
External I/O Ports	
USB	5 , 2 x USB 3.0 + 3 x USB2.0
Add-on Module Slot	1
Stand I/O Ports	
Com port	2 x RJ45 (0V / 5V / 12V selection by Jumper setting ,default 0V)
LAN	1 x 10/100/1000Mbps
USB	2 x USB 2.0
Cash drawer	1 x RJ-11 (12V/24V)
DC Input	1 x 24V DC or 12V DC (without printer)
Built-in Device	
Speakers	2 x 2W
Digital Mic	1
AD/DC adapter	24V/100W adapter or 12V/60W adapter (without printer)
Optional Peripherals	
NFC/RFID	13.56 MHz
Scanner	2D Barcode Scanner
MSR	3-Track MSR module
Second display	7" or 10" LCD display
Thermal printer	Paper roll dia. Width 58/80 mm, 170 mm/s, out of paper sensor, auto cutter
Wireless Communication	
Wi-Fi	802.11 b/g/n (option)
Bluetooth	BT4.0 (option)
OS Support	
Windows	Windows Embedded Industry 8.1 (64bit), Win 10 IoT (64bit)
Linux	Per Request

Features and specifications are subject to change without prior notice.

CONTACT

LONGSHINE Technologie GmbH

Headquarters:

An der Strusbek 9, 22926 Ahrensburg, Germany No 945 Boai Street, Jubei City, Hsinchu, Taiwan 30265 TEL: +49 4102 49220 FAX: +49 4102 40109 www.longshine.de