



**NQuire 350
Skate**
micro kiosks

Features

Self-Scanning focused.

The NQuire 350 Skate is armed with a 2D omni-directional scan engine. Its megapixel scanner easily reads barcodes, no matter the size or material that it's been printed on. A 20 degree angle of the reader makes scanning larger products comfortable. For digital barcodes, this same tilt guides each user to present their smart phone at the optimal angle to combat reflection.

Heavily customized Android OS for easy integration and Device Management.

Running on Android 7.1, the NQuire 350 Skate ensures intuitive navigation to your customers and your team. Looking up product information, scanning tickets or checking prices is quick and simple. Meanwhile software and development possibilities are as powerful and widespread as they are in larger equivalents.

Greater visibility.

Newland's MDM Ndevor, included with each NQuire 350 Skate, makes updating and maintaining devices even easier by connecting them to a cloud- based configuration and monitoring tool.

Endless communication possibilities.

The NQuire 350 Skate is equipped with a variety of features that make it easy to adapt the micro kiosk to your application. The device has a built-in RFID reader and data can be transmitted through Ethernet, WiFi and Bluetooth. An external USB and GPIO port provides the possibility to connect an external device, such as a handheld scanner.

Mount anywhere.

With its small footprint and VESA 75 compliant design, the NQuire 350 Skate can be mounted on any shelf, pole or wall.

Backwards compatible.

The NQuire 350 Skate's embedded CIT emulation program means the device can emulate the exact functions of the NQuire 200 series. Enabling prior customers to explore what's possible with Android while they continue their existing processes.



Application Scenarios



access control



retail



self service

NQuire 350 Skate technical specifications

Performance	Operating System	Android 7.1
	Processor	1.5GHz Octa-core
	Memory RAM	2GB
	Memory Flash	8GB
	Memory Storage Expansion (Max.)	Supports Micro SD up to 128GB
Data capture	1D	Code 11, Code 128, Code 39, GS1 128 (UCC/EAN-128), AMI 128, Codabar, ISBT 128, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, ITF14, ITF6, Industrial 25, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS), Code 49, Code 16K, etc.
	2D	PDF417, QR Code, Micro QR, Data Matrix, Aztec, MaxiCode, GM Code, Chinese Sensible Code, MicroPDF417, Code One
Physical	Dimensions (mm)	140(H) x 139.5(W) x 61(D) mm
	Weight	403g
	VESA	Complies with standard 75 bracket, enabling easy mounting on shelves and walls
	Display	4.3" 480x272 TFT LCD Display with capacitive touch panel
	Touch panel	Capacitive touch panel
	Interfaces	USB: 2 x USB2.0 ports (one supports host, other supports host & slave); GPIO: Programmable GPIO (2 in - 2 out)
	Power Consumption	6W
	Power Supply Input	AC110 ~ 220V, 50~60Hz
	Power Supply Output	DC12V, 2A
	Power over Ethernet	IEEE 802.3af
	Audio	88dB (850Hz~20KHz) dual-channel stereo sound
	Expansion Slot	Micro SD up to 128GB
Environmental	Operating Temperature	0°C to 50°C (32°F to 122°F)
	Storage Temperature	-20°C to 55°C (-4°F to 131°F)
	Humidity	Operating: 5% to 90% (non-condensing) Storage: 5% to 95% (non-condensing)
Wireless	WLAN Radio	IEEE 802.11a/b/g/n/ac
	WPAN Radio	Bluetooth 4.0 LE
	RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FelCa
Warranty	Warranty	2 years