

# MicroKiosk

## PMK-170 KS



### MicroKiosk PMK-170 KS

- Both cost-effective and high-performance platforms are available
- 15" and 17" TFT LCD available with 5-wired resistive touch panel technology (optional: SAW Touch)
- Fanless design (FT series) allows terminal to be implemented into a high range of environment
- Good flexibility design suitable for various applications
- 15" or 17" screen with optional omni-directional scanner and speakers
- Extremely solid and reliable structure
- Water spill resist from the front bezel
- Power switch and LCD brightness control panel
- Hidden connector and power cable design
- Optional CF socket functionality (FT series) for thin client application
- Tool free easy maintenance design (CT series)



15" or 17" screen  
with optional  
omni-directional  
scanner and speakers



Tool free easy  
maintenance  
hatch back  
design




Optional  
USB  
on the side



Extremely solid  
and reliable structure  
with 75mm VESA  
holes for wall mounting  
capability



Wires are connected  
downward for space saving



**KONCEPT-L**  
SPÓŁKA AKCYJNA

SYSTEMY AUTOMATYCZNEJ IDENTYFIKACJI

# MicroKiosk

## PMK-170 KS



### Specification

|                            |                   |                                                                                                           |
|----------------------------|-------------------|-----------------------------------------------------------------------------------------------------------|
| Motherboard                | CPU               | Intel Celeron M. 2.0GHz<br>or Intel Atom D410                                                             |
|                            | Memory            | DDRII x 2 (2GB up to 4GB)                                                                                 |
|                            | Video             | Intel 960GLE or Intel 3150GMA                                                                             |
|                            | Ethernet          | 10/100/1000Mbps                                                                                           |
| HDD                        |                   | 2,5 SATA HDD or SSD x 1                                                                                   |
| Display                    | LCD Size          | 15" XGA or 17" SXGA                                                                                       |
|                            | Brightness        | 250-350 cd/m <sub>2</sub>                                                                                 |
|                            | Resolution        | 1024x768 or 1280x1024                                                                                     |
|                            | Touch Screen Type | 5-wired Resistive, capacitive or SAW                                                                      |
| I/O Port                   | Serial Port       | RS-232 x 4                                                                                                |
|                            | Parallel          | 1                                                                                                         |
|                            | USB               | USB2.0 x 4                                                                                                |
|                            | PS/2 Port         | 1 x keyboard, 1 x Mouse                                                                                   |
|                            | VGA Port          | 1                                                                                                         |
|                            | Ethernet Port     | RJ-45 x 1                                                                                                 |
|                            | Audio Port        | 1 x Line-out, 1 x Mic-in                                                                                  |
|                            | Expansion Slot    | MiniPCI x 1                                                                                               |
| Diameter                   |                   | 430 x 420 x 100 mm                                                                                        |
| Optional Integrated Device |                   | Omni-Directional Laser Scanner<br>MSR or Fingerprint Sensor<br>3-in-1 MSR/ICC/IBT Reader<br>Sound Speaker |



**KONCEPT-L**  
 SPÓŁKA AKCYJNA

**KONCEPT-L SPÓŁKA AKCYJNA**

ul. Odrowąża 15 • 03-310 Warszawa • tel. +4822 512 79 00 • fax +4822 512 79 01  
 e-mail: [koncept@koncept-L.pl](mailto:koncept@koncept-L.pl) • [www.koncept-L.pl](http://www.koncept-L.pl)